



# Amika

# undercounter glasswashers



**35 XL**



**40 XL**



**45 XL**



**51 XL & 55 XL WSD**

(see next page for 50 XL image)

- 1 year warranty
- Halcyon Amika models ruggedly built with simple controls
- 55 XL WSD with internal automatic water softener
- Large three button controls on 35 XL, 40 XL, 45 XL & 50 XL
- Simple soft touch wipe clean controls on 51 XL & 55 XL WSD
- All models fitted as standard with precise control peristaltic detergent and rinse aid dosing
- Drain pump as standard on 55 XL WSD, optional on all other models
- Surface scrap trays standard on 45 XL
- Surface scrap trays optional on 50 XL, 51 XL & 55 XL WSD
- 51 XL & 55 XL WSD with internal breaktank as standard

## Technical

- Standard voltage 240V – single phase
- 50 XL, 51 XL & 55 XL WSD can be supplied for 3 phase operation
- Suitable for hot (max 50°C) or cold\* water supply at 2 to 4 bar dynamic pressure
- Wash temperature 60°C
- Rinse temperature for 35 XL, 40 XL, 45 XL & 50 XL 65°C
- Rinse temperature for 51 XL & 55 XL WSD 80°C

Drain pump versions require a waste up-stand for correct operation. Restrictive waste connections should be avoided for all installations.

\*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Time Sec	Power kW	Amps Required
AM 35 XL	350	255	400 x 480 x 630#	120	2.9	13
AM 35 XLD		As AM 35 XL above with fitted drain pump				
AM 40 XL	390	285	440 x 530 x 645#	120	2.9	13
AM 40 XLD		As AM 40 XL above with fitted drain pump				
AM 45 XL	450	255	530 x 560 x 700#	120	2.9	13
AM 45 XLD		As AM 45 XL above with fitted drain pump				
AM 50 XL	500	325	580 x 605 x 815#	90/150	2.6/4.5/6.5	13/20/30##
AM 50 XLD		As AM 50 XL above with fitted drain pump				
AM 51 XL	500	325	580 x 605 x 815#	90/150	2.6/4.5/6.5	13/20/30##
AM 51 XLD		As Am 51 XL above with fitted drain pump				
AM 55 XL WSD	500	325	580 x 605 x 815#	90/150	2.6/4.5/6.5	13/20/30##
AM 55 XL WSD supplied with drain pump as standard						

# Height excludes feet which add 10 to 20mm.

## Machines will be supplied for 30 amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

It is strongly recommended that for busy sites to achieve optimum performance that machines are installed on hot fill (max 50°C).