


# C Range | pass through + heat recovery



dishwashers



**C1035 WS HR**  
(shown with tableting –  
not included)

- n ■ 2 year warranty
- n ■ **HEAT RECOVERY**
- n ■ **Up to 25% less power required to heat rinse water**
- n ■ **HR module supplied separately with simple bolt on instructions**
- n ■ Reduces need for extraction hood and improves working environment
- n ■ Breaktank type AA
- n ■ Internal automatic water softener
- n ■ Bright LED display with soft touch controls
- n ■ Accurate detergent and rinse aid peristaltic dosing as standard
- n ■ Drain pump fitted as standard
- n ■ Patented DUAL flow wash pump, reduced power while retaining wash efficiency
- n ■ Three selectable cycle options plus special application cycles options
- n ■ Cycle times can be tailored to site requirements
- n ■ Selectable energy saving mode
- n ■ Selectable thermostop ensures optimum rinse temperatures
- n ■ Automatic self-cleaning cycle at end of service
- n ■ Surface scrap tray filters
- n ■ Operational self-diagnostics
- n ■ Twin traffic light display indicates machine status
- n ■ Supplied with one pegged plate, one open rack and cutlery basket

## Technical

- n ■ Standard voltage 240V – single phase  
(can be supplied for 3 phase)
- n ■ Suitable for cold\* water supply only at 2 to 4 bar dynamic supply pressure. Cannot be used with hot water supply.
- n ■ Wash temperature 60°C (adjustable)
- n ■ Rinse temperature 78°C (adjustable)
- n ■ Cycle times between 70 & 240 secs

Drain pump versions require a waste up-stand for correct operation.

Restrictive waste connections should be avoided for all installations.

\*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.



Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required
<b>C1035 WS HR</b>	500	380	640 x 740 x 2150 <sup>#</sup>	3 Cycles	6.5/4.5	20/30 <sup>##</sup>

# Height adjustable from 2150 to 2205mm.

## Machines will be supplied for 30 amp supply as standard, if 20 amp required specify at time of order.