



M22-5



M30-10



M34-16



M42-16



M50-25



M65-40



M90-55



M130-65



M155-65

- 3 year warranty
- All models are WRAS approved
- Four models now with fitted drain pump option M50-25 DP, M65-40 DP, M90-55 DP & M130-65 DP
- All models use a spray system that minimises scaling and produces separate cubes of crystal clear ice which are slow melting
- Capable of operating in ambient temperatures of between 10°C and 43°C
- Supply water temperature between 3°C and 32°C
- Easy clean ice storage in tough ABS
- All models (except M22-5 13 grams only) are available to special order for the production of cubes of 13 and 33 grams

For maximum production at high ambient temperatures all models are available to special order as water cooled versions at the same price.

## Technical

- Voltage 240V – single phase – 13 amp
- All models supplied with UK 3 pin moulded plug
- Require water supply pressure between 1 and 6 bar
- Optimum ice production is at an ambient temperature of 21°C. Higher temperatures will dramatically reduce ice production

To produce ice of good quality all ice machines must be supplied with suitably softened and filtered water. Any filters and softeners must be of sufficient capacity and correctly maintained.

| Model      | Production Kgs per 24hrs  | Bin Capacity Kgs | Storage Capacity x Standard Cube Size | Dimensions mm W x D x H (inc. feet) | Drain Height (inc. feet) mm | Water Consumption (air cooled) Litres/Kg | Water Consumption (water cooled) Litres/Kg |
|------------|---|------------------|---------------------------------------|-------------------------------------|-----------------------------|--|--|
| M22-5      | 21  | 5                | 310 x 13g                             | 345 x 400 x 595                     | 143                         | 4.5                                      | 20   |
| M30-10     | 28  | 10               | 530 x 18g                             | 390 x 460 x 695                     | 135                         | 5.1                                      | 14   |
| M34-16     | 34  | 16               | 950 x 18g                             | 500 x 580 x 790                     | 261                         | 3.3                                      | 13   |
| M34-16 DP  | As M34-16 above with fitted drain pump (Not available as water cooled)  |                  |                                       |                                     |                             |  |  |
| M42-16     | 42  | 16               | 950 x 18g                             | 500 x 580 x 790                     | 261                         | 4.0                                      | 15   |
| M42-16 DP  | As M42-16 above with fitted drain pump (Not available as water cooled)  |                  |                                       |                                     |                             |  |  |
| M50-25     | 48  | 25               | 1470 x 18g                            | 500 x 580 x 900                     | 261                         | 4.0                                      | 14   |
| M50-25 DP  | As M50-25 above with fitted drain pump (Not available as water cooled)  |                  |                                       |                                     |                             |  |  |
| M65-40     | 65  | 40               | 2350 x 18g                            | 738 x 600 x 1020                    | 350                         | 2.8                                      | 12.8                                       |
| M65-40 DP  | As M65-40 above with fitted drain pump (Not available as water cooled)  |                  |                                       |                                     |                             |  |  |
| M90-55     | 90  | 55               | 3240 x 18g                            | 738 x 600 x 1120                    | 350                         | 2.5                                      | 14.2                                       |
| M90-55 DP  | As M90-55 above with fitted drain pump (Not available as water cooled)  |                  |                                       |                                     |                             |  |  |
| M130-65    | 130   | 65               | 3830 x 18g                            | 840 x 740 x 1175                    | 355                         | 2.8                                      | 15.3                                       |
| M130-65 DP | As M130-65 above with fitted drain pump (Not available as water cooled) |                  |                                       |                                     |                             |  |  |
| M155-65    | 155   | 65               | 3830 x 18g                            | 840 x 740 x 1175                    | 355                         | 2.6                                      | 13   |