

D Range | undercounter



dishwashers



D511



D515 WS

- n ■ 2 year warranty
- n ■ D515 WS with internal automatic water softener
- n ■ Breaktank as standard
- n ■ Drain pump fitted as standard on all models
- n ■ Moulded wash tank designed for easy cleaning and reduced water usage
- n ■ Low running costs due to improved rinse efficiency
- n ■ Surface scrap trays as standard
- n ■ Soft touch controls with bright LED display
- n ■ Twin traffic light display indicates machine status
- n ■ Accurate detergent and rinse aid peristaltic dosing as standard
- n ■ Three selectable cycle options plus special application cycles options
- n ■ Selectable GLASS cycle to change operation for glass washing
- n ■ Selectable GREEN cycle for minimum energy usage
- n ■ Automatic self-cleaning cycle
- n ■ Full double skinned for noise and reduced heat loss
- n ■ One open/cup, one pegged rack and cutlery insert as standard
- n ■ All machines are supplied with two racks

Technical

- n ■ Standard voltage 240V – single phase
- n ■ Models can be supplied for 3 phase
- n ■ Suitable for hot (max 50°C) or cold* water supply at 2 to 4 bar dynamic supply pressure
- n ■ Wash temperature 60°C (adjustable)
- n ■ Rinse temperature 78°C (adjustable)
- n ■ Cycle times between 70 & 240 secs, dependent on model

Drain pump versions require a waste up-stand for correct operation.

Restrictive waste connections should be avoided for all installations.

*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.



Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Options	Power kW	Amps Required
D511	500	355	600 x 605 x 815 [#]	3 Cycles	2.6/4.5/6.5	13/20/30 ^{##}
D515 WS	500	355	600 x 605 x 815 [#]	3 Cycles	2.6/4.5/6.5	13/20/30 ^{##}

Height excludes adjustable feet which will add 10 to 20mm.

Machines will be supplied for 30 amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.