

Washer extractor

QuickWash

Features and benefits

- A knob for simple programme selection and start
- Large, clear display
- AWS – Automatic Weighing System with Compass Control – determine the wash load and adopt the water intake accordingly. Savings on water and energy if machine is not fully loaded
- Front-mounted detergent drawer with four compartments for powder or liquid detergent
- High extraction force for efficient dewatering
- Panels and frame made from galvanized steel
- Inner and outer drums made from stainless steel
- Powder coated black front panel, side panels and top cover
- Strong door and hinges. Easy-grip, ergonomic door handle which makes the door easy to open and close
- Drain pump
- Frequency-controlled motor with no carbon or brushes
- Door seal in the door, does not wear when the machine is loaded and unloaded



Main options

- This machine can be upgraded to include the “Towel” programme range for washing very dirty towels, cloths or clothes
- Stacking kit to install tumble dryer QuickDry on top to save space
- Plinths for raising the machine to a comfortable height (height 100 mm when installed with a tumble dryer, or 290 mm)
- Connecting hoses

Main specifications		QuickWash
Max. capacity	kg	5.5
Drum, volume	litre	53
diameter	ø mm	452
Extraction	rpm	1300
G-factor		425
Heating alternatives, electricity	kW	4.4 / 2.2 / 2.8
Consumption data "Normal 60°C" *		
Total time	min	44 / 56 / 50
Water consumption	litre	67
Energy consumption (motor/heating)	kWh	0.15/0.85
* Water temperature 15°C cold water.		

Electrical connections*			QuickWash
Heating	Voltage		
EI.	400V 3NAC 50 Hz	kW(A)	4.7 (10)
	240V 1NAC 50 Hz	kW(A)	2.4 (13)
	240V 1NAC 50 Hz	kW(A)	3.1 (13)
Water connections			
Water valves	DN		20
Water pressure	kPa		200-500
Capacity at 300 kPa	l/min		17
Draining capacity	l/min		25
Max. draining	l		20
Floor requirements			
Frequency of the dynamic force	Hz		20
Max floor load at extraction	kN		1.02±0.3
Sound levels			
Sound power level**	dB(A)		68
Heat emission			
% of installed power, max			5
Shipping data			
	net, kg		99
	crated, kg		109
Shipping volume	m ³		0.47
Accessories			
Stacking kit with QuickDry			x
Stainless base, 290 mm, and galvanised base for stacking installation, 100 mm			x
Dimensions in mm			
A Width			595
B Depth			680
C Height			850
D			305
E			660
F			80
G			60
H			90
I			80
K			650 ± 50
1 Control panel 2 Soap box 3 Door opening ø255 4 Cold water 5 Drain, pump 6 Electrical connection			

* Other voltages available, see installation manual

** According to IEC 60704

